



THE BIG FELLA INSTALL GUIDE



PREFACE

INSTALLING THE BIG FELLA REQUIRES MODERATE TRADE SKILLS

PLEASE READ THIS MANUAL PRIOR TO UNDERTAKING THE INSTALLATION TO ENSURE YOU ARE PROPERLY PREPARED TO COMPLETE THE JOB

TOOLS REQUIRED:

- BATTERY DRILL
- DRILL BITS (3MM AND 4.5MM)
- RIVET GUN
- PHILLIPS HEAD SCREWDRIVER



THE MOUNTING KIT

YOUR BIG FELLA WILL COME WITH ALL OF THE NECESSARY HARDWARE FOR MOUNTING TO YOUR TROOPY:

- 8X BLACK 4MM RIVETS
- 1X 3.5MM PHILLIPS HEAD SCREW
- 2X BLACK SLIDE TRACKS



STEP 1

USING THE SHORT SLIDE TRACK AS A GUIDE, DRILL YOUR FIRST 4.5MM HOLE AND MOUNT THE TRACK IN PLACE WITH A RIVET, ENSURING THAT THE HOLE IS DRILLED IN THE CENTRE OF THE DOOR FRAME

NOTE THAT LEFT EDGE OF THE TRACK IS UP AGAINST THE CORNER WELD



STEP 2

USING THE SLIDE TRACK AS A GUIDE, DRILL AND RIVET THE REMAINING MOUNTING POINTS



STEP 3

SLIDE THE BIG FELLA INTO THE TRACK



STEP 4

SLIDE THE LONGER TRACK ONTO THE BOTTOM OF THE BIG FELLA



STEP 5

WHILE PULLING THE BIG FELLA TIGHT SO THERE IS NO SAGGING, USE THE BOTTOM TRACK AS A GUIDE TO DRILL AND RIVET IT IN PLACE, ENSURING THAT THE TRACK IS RUNNING PARALLEL TO THE TOP EDGE OF THE DOOR CARD BELOW

NOTE THAT THE RIGHT EDGE OF THE TRACK SITS FLUSH UP AGAINST THE PLASTIC DOOR LATCH SHROUD



STEP 6 (OPTIONAL)

IF YOU WISH TO SECURE THE BIG FELLA IN PLACE YOU CAN DRILL A 3MM HOLE ANYWHERE ON THE SLIDE TRACK AND INSERT THE PHILLIPS HEAD SCREW

THIS WILL PREVENT THE BAG MOVING FROM SIDE TO SIDE

USE PLENTY OF PRESSURE AND TAKE YOUR TIME INSERTING THE SCREW TO ALLOW FOR THE THREAD TO CUT INTO THE TRACK



STEP 7

STEP BACK, CRACK A COLD TINNIE AND BE PROUD OF THE LATEST ADDITION
TO YOUR BELOVED TROOPY

IT'S TIME TO FILL YOUR BIG FELLA WITH HANDY ITEMS THAT WILL MAKE LIFE
EASIER ON THE ROAD



BEFORE YOU GO

JUST A FEW NOTES TO HELP YOU GET THE BEST OUT OF YOUR BIG FELLA:

PLEASE DO NOT OVERLOAD THE BAGS AS THIS WILL RESULT IN UNDUE STRESS
ON THE MOUNTING SYSTEM

DO NOT PULL ON THE BAG OR THE SLIDE TRACK FROM INSIDE THE VEHICLE TO
CLOSE THE DOOR

WE RECOMMEND MAINTAINING THE ZIPS AND SLIDERS WITH A SILICONE SPRAY
LUBRICANT AT LEAST EVERY 6 MONTHS, ESPECIALLY IN HARSH ENVIRONMENTS

